

Piastra ad induzione PRO 3500

Struttura in acciaio inox - Vetroceramica Schott Ceran® - Timer, livello di potenza e temperatura regolabili individualmente - Sensore presenza pentola - 10 livelli di potenza - Timer da 1 a 180 minuti regolabile ad intervalli di 1 minuto - Selezione temperatura da 60 °C a 240 °C - Protezione termica - Doppia ventola di raffreddamento con filtro - Display digitale.

PRO 3500 induction cooker

Stainless steel structure - Schott Ceran® ceramic glass - Timer, power levels and temperature individually adjustable - Automatic pot detection - 10 power levels - Timer function 1 – 180 minutes in 1 minute intervals - Temperature pre-selection approx - 60 °C – 240 °C. Safety switch for overheating protection - Dual cooling fans with filter - Digital display.



3500 Watt



PRO 3500

MODELLO MODEL	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	DIMENSIONI mm DIMENSIONS mm	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm
PC PRO 3500	3500	230/1N/50	355x440x120h	6,4	8,0	44x54x20h